

KANATOL - FLAMEGUARD P 100

TRI PHENYL PHOSPHATE (TPPA) Phosphate plasticizer




Chemical Nature Phosphoric Acid Triphenyl Ester

Chemical name :- TRI PHENYL PHOSPHATE Trade Name :- FLAMEGUARD 66

Molecular Formula :- (C₆H₅O)₃ PO Molecular weight :- 326.29 g/mole

Molecular Structure



CAS Number :- 115-86-6 UN. NO. :- 3082 EINECS NO. :- 204-212-2

Specification

Characteristics	Unit	Test Method	Value
Appearance		Visual	White Crystline Flakes
Colour	HU	ASTM-D-1045-86	25 max.
Specific Gravity (60°C)	_	ASTM-D-1045	1.208.
Acidity	wt.%	ASTM-D-1613	0.01 max.
Moisture	wt.%	K.F.ASTM-E-203-01	0.10 max.
Free Alcohol	%	KOR/QCD/FP-3.4	0.05 max.
Ester Content	%	GLC KOR/QCD/FP-4.	7 99.00 min.
Viscosity (60°C)	cps	Brook Field ASTM D- 445	17.00.
Melting Point	°C	IS-5762 : 1970	47.5-49.5
Water Soluble Impurities p' Content	ppm %	BS :1998 :1970 KOR/QCD/FP-3.8	10 max. 9.40-9.50
p Content	70	KUR/QUD/FF-3.0	9.40-9.50

Properties

TPPA is the colour less solid, usually sold in a flaked form (mp. 48-490C), TPPA is the general purpose monomeric naturally derived triartryl phosphate. It is most widely used among natural Phosphate Ester due to characteristics like weather resistance, fire retardancy, good flexibility and low solubility in water.

Total Solution in Plasticizers

Contact: plasticizer@kljindia.com

An ISO 9001:2000 and ISO 14001:2004 conglomerate

www. kljindia.com





KANATOL - FLAMEGUARD P 100

Application

TPPA is used as a flame retardant plasticizer for cellulose acetate, photographic safety field which is its major use. Also used as a flame retardant additive in cellulose nitrile, engineering thermoplastic and rigid urethane form. Where compatibility is limited with pure tri phenyl phosphate combination with other plasticizer such as phthalates are used

Packing & Storage

TPPA is packed in 25/50 kg paper drum / bag. It is stored in tightly closed container, in a cool & dry, ventilated area.

Shelf life

Original characteristics remain intact for a period of 24 months, if kept in recommended storage.

Safety

The MSDS can be provided on request.

Disclaimer

The data contained in this publication are based on our current knowledge and experience. During processing, there are so many factors which may affect the application part of TPPA, so these data neither imply any guarantee of certain properties, nor the suitability of the product for the specific purpose. Any data given in this publication may change without prior information and do not constitute the agreed quality of our product.

Total Solution in Plasticizers

Contact: plasticizer@kljindia.com

An ISO 9001:2000 and ISO 14001:2004 conglomerate

www. kljindia.com